Patent Abstracts of Japan

PUBLICATION NUMBER .

: JP7131322

E A N

PUBLICATION DATE

: 19-05-1995

APPLICATION NUMBER

: JP19930270542

APPLICATION DATE

: 28-10-1993

VOL: 1995

NO: 8

AB. DATE

PAT: A 7131322 : 29-09-1995

PATENTEE

: TEC CORP

PATENT DATE: 19-05-1995

INVENTOR : UCHIDA HIROSHI

INT.CL.

: H03K17/96

TITLE

: TOUCH CHANGEOVER SWITCH

CIRCUIT

ABSTRACT

: PURPOSE: To turn on/off an FF output corresponding to the touch noise voltage of a touch terminal by outputting a high-order signal from a comparator when a divided voltage exceeds a reference voltage, smoothing that output with a capacitor and performing an inverting operation at a JKFF in response to this

smoothed signal.

CONSTITUTION: When a human body touches a touch terminal 21, a noise-shaped fine current flows from the tip of a finger through resistors 22 and 23, and the noise-shaped divided voltage to be aV at a maximum is generated at a junction (t) of the resistors 22 and 23. Then, a comparator 24 outputs a pulse- shaped signal which becomes the high-order signal only when the divided voltage exceeds a reference voltage sh. This voltage is smoothed by a capacitor 30, and the smoothed signal in the shape of a rectangular wave is inputted to a clock input terminal CL of a J-KFF 31. This FF 31 outputs a rectangular wave signal from an output terminal Q by performing the inverting operation in response to the rise of the smoothed signal. Namely, the output signal from the output terminal Q of the J-KFF 31 is alternately inverted to the high order and the low order at the time of first touch after a power source is turned on, and a load connecting terminal 36 is switched.

セット信号

Japanese Patent Publication No. 7131322

2/9/1

DIALOG(R) File 351: DERWENT WPI

(c) 2000 Derwent Info Ltd. All rts. reserv.

010318186 **Image available**
WPI Acc No: 1995-219449/199529

XRPX Acc No: N95-172220

Touch switch circuit e.g. for controlling luminaire - uses voltage divider network, reference voltage generator, comparator and capacitor to toggle JK flip-flop on touching touch terminal and produce output accordingly

Patent Assignee: TOKYO ELECTRIC CO LTD (TODK)
Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
JP 7131322 A 19950519 JP 93270542 A 19931028 199529 B

Priority Applications (No Type Date): JP 93270542 A 19931028 Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes JP 7131322 A 5 H03K-017/96

Abstract (Basic): JP 7131322 A

The switching circuit employs a voltage divider network comprises of resistor (22, 23). The reference voltage is obtained through another divider network consisting of one fixed value resistor (25) and one variable resistor (26). The reference voltage and the voltage signal obtained from centre tap (t) of the first divider network connected to touch terminal (21) are fed to a comparator (24).

When the divider output voltage exceeds the reference voltage the comparator outputs a high level signal to a smoothing capacitor (30). This smoothed and filtered signal is then fed to a clock terminal (CL) of a flip flop (31). The JK flip flop in turn toggles ON or OFF accordingly to its previous state.

ADVANTAGE - Reduces variation in touch-sensitivity. Dwg.1/6

Title Terms: TOUCH; SWITCH; CIRCUIT; CONTROL; LUMINAIRE; VOLTAGE; DIVIDE; NETWORK; REFERENCE; VOLTAGE; GENERATOR; COMPARATOR; CAPACITOR; TOGGLE; JK; FLIP-FLOP; TOUCH; TOUCH; TERMINAL; PRODUCE; OUTPUT; ACCORD

Derwent Class: U21; X26

International Patent Class (Main): H03K-017/96

File Segment: EPI

Manual Codes (EPI/S-X): U21-B02C1; X26-C03